

AMC 133X™

VISCOSIFIERS



Description

AMC 133X™ is a rapidly yielding, high molecular weight polymer in liquid form that provides viscosity without the problems associated with mixing powdered polymers. AMC 133X™ will help improve core recovery, particularly in clays and shales and highly fractured formations. It provides cuttings encapsulation as well as helping to stabilise the formation.

Application

AMC 133X™ may be used to prepare a solids free drilling fluid system; it exerts similar properties to powder polymers such as AMC CR 650™. It can be used as a single product, low solids fluid, or it can be combined with AMC GEL™ or other polymers such as AMC PAC™ to form a more robust mud system. It can also be used with other clay and shale stabilizers such as potassium chloride or AMC SHALEHIB ULTRA™ to give a high degree of clay or shale stabilisation, although higher concentrations may be required to maintain viscosity.

Typical Physical Properties

Appearance: Light blue liquid
 Specific gravity: 1.05 – 1.15
 Molecular charge: Anionic

Recommended Treatment

Under normal conditions AMC 133X™ can be mixed at 0.75 – 1.5L / m³ (0.25 – 0.6lb / bbl) of make-up water. Concentrations should be varied to provide optimum viscosity for cuttings removal and efficient encapsulation of cuttings. 0.5 – 0.75L / m³ (0.15 – 0.3lb / bbl) can be used to reduce rod vibration and torque.

Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.

Advantages

- Easily mixed in low shear environments
- Controls sticky clays and inhibits water sensitive, swelling formations
- Promotes effective settling of drilling solids in surface pits
- Reduces rod vibration and torque
- Easily broken down for the development of water wells after setting screens
- Economical to use.

ASIA PACIFIC

Perth, Australia (Head Office)

T +61 8 9445 4000
 E amc@imdexlimited.com

Indonesia

T +62 (0) 21 759 11244

AFRICA

South Africa

T +27 (11) 908 5595

EUROPE

Germany

T +49 4402 6950-0

United Kingdom

T +44 (0) 1273 405 975

SOUTH AMERICA

Argentina

T +54 (9) 261 426 1116

Brazil

T +55 (47) 3404 5920

Chile

T +56 (2) 2589 9300

Peru

T + 51 (1) 322 8850

NORTH AMERICA

USA / Canada

T +801-364-0233

Mexico

T +52 (871) 169 2095