

AMC BEN™

VISCOSIFIERS



Description

AMC BEN™ is a high quality sodium bentonite for use in mineral exploration, water well and directional drilling which meets or surpasses the API 13A test specifications.

Application

AMC BEN™ is an effective viscosifier in fresh and brackish water. It provides good filtrate control and is an excellent product for use in the construction and civil engineering industries. AMC BEN™ has a consistent quality and can be used in conjunction with all other drilling mud products.

Typical Physical Properties

Appearance: Light grey to brown powder
 Solubility: Insoluble in water
 Specific gravity: 2.4 – 2.6

Recommended Treatment

APPLICATION	KG / M ³	LB / BBL
Normal drilling conditions	0 – 60	0 – 21
Unconsolidated, caving formations	70 – 90	25 – 32
Lost circulation	80 – 100	28 – 35

Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.

Advantages

- Helps to improve hole cleaning
- Provides hole stability in poorly consolidated formations
- Mixes easily
- Economical

ASIA PACIFIC

Perth, Australia (Head Office)

T +61 8 9445 4000
 E amc@imdexlimited.com

Indonesia

T +62 (0) 21 759 11244

AFRICA

South Africa

T +27 (11) 908 5595

EUROPE

Germany

T +49 4402 6950-0

United Kingdom

T +44 (0) 1273 405 975

SOUTH AMERICA

Argentina

T +54 (9) 261 426 1116

Brazil

T +55 (47) 3404 5920

Chile

T +56 (2) 2589 9300

Peru

T + 51 (1) 322 8850

NORTH AMERICA

USA / Canada

T +801-364-0233

Mexico

T +52 (871) 169 2095