

# AMC BEN XTRA™

## VISCOSIFIERS



### Description

AMC BEN XTRA™ is a premium grade Wyoming sodium bentonite which meets or surpasses the API 13A test specifications for drilling grade bentonite.

### Application

AMC BEN XTRA™ is an effective viscosifier in fresh and brackish water. It provides good filtrate control and is an excellent product for use in the construction and civil engineering industries. AMC BEN XTRA™ has a consistent quality and can be used in conjunction with all other drilling mud products.

### Typical Physical Properties

Appearance: Light grey to brown powder  
 Solubility: Insoluble in water  
 Specific gravity: 2.4 – 2.6

### Recommended Treatment

APPLICATION	KG / M <sup>3</sup>	LB / BBL
Normal drilling conditions	0 – 60	0 – 21
Unconsolidated, caving formations	70 – 90	25 – 32
Lost circulation	80 – 100	28 – 35

*Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.*

### Advantages

- Helps to improve hole cleaning
- Provides hole stability in poorly consolidated formations
- Mixes easily
- Economical.

#### ASIA PACIFIC

Perth, Australia (Head Office)

T +61 8 9445 4000  
 E amc@imdexlimited.com

Indonesia

T +62 (0) 21 759 11244

#### AFRICA

South Africa

T +27 (11) 908 5595

#### EUROPE

Germany

T +49 4402 6950-0

United Kingdom

T +44 (0) 1273 405 975

#### SOUTH AMERICA

Argentina

T +54 (9) 261 426 1116

Brazil

T +55 (47) 3404 5920

Chile

T +56 (2) 2589 9300

Peru

T + 51 (1) 322 8850

#### NORTH AMERICA

USA / Canada

T +801-364-0233

Mexico

T +52 (871) 169 2095