

AMC DRTG ZN50™

LUBRICANTS & CUTTING OILS



Description

AMC DRTG ZN50™ is a heavy duty, high performance thread compound containing 50% metallic zinc, thickening agents and proprietary additives. AMC DRTG ZN50™ is a No. 2 consistency grease designed to reduce galling, friction and minimise wear. AMC DRTG ZN50™ is extremely tenacious and will adhere to all metal surfaces, is resistant to water wash and helps prevent corrosion.

Application

AMC DRTG ZN50™ is applied generously to the tool joints and threaded sections of drill pipe, normally applied with a brush, spatula or suitable item.

Typical Physical Properties

Appearance:	Smooth grey with tacky consistency
Base oil viscosity:	(cst @ 40°C) 185 (cst @ 100°C) 41.6
Dropping point:	265
Operating temp (°C):	-25 to 140
Penetration @ 25°C worked:	280
Flashpoint (°C, OC):	200

Recommended Treatment

Apply generously to the tool joints and threaded sections of drill pipe.

Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.

Advantages

- Easily applied
- Resistant to high temperatures
- Exceptional adhesion characteristics
- Minimises wear
- Preventative towards corrosion.

ASIA PACIFIC

Perth, Australia (Head Office)

T +61 8 9445 4000

E amc@imdexlimited.com

Indonesia

T +62 (0) 21 759 11244

AFRICA

South Africa

T +27 (11) 908 5595

EUROPE

Germany

T +49 4402 6950-0

United Kingdom

T +44 (0) 1273 405 975

SOUTH AMERICA

Argentina

T +54 (9) 261 426 1116

Brazil

T +55 (47) 3404 5920

Chile

T +56 (2) 2589 9300

Peru

T + 51 (1) 322 8850

NORTH AMERICA

USA / Canada

T +801-364-0233

Mexico

T +52 (871) 169 2095