

AMC WATER CONDITIONER™

TREATING CHEMICALS



Description

AMC WATER CONDITIONER™ is a blend of water treating agents used for the treatment of water containing large amounts of magnesium, calcium and other metal ions that have a detrimental effect on the yield of drilling fluid additives such as bentonite or polymers.

Application

Addition of AMC WATER CONDITIONER™ should always be done prior to addition of polymers or bentonite when the make-up water quality is known to be poor.

Typical Physical Properties

Appearance: White flakes
Solubility: Soluble in water

Recommended Treatment

Use 1 kg / m³ for every 100 mg / L of total hardness.

Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.

Advantages

- Negates the need to use high concentrations of AMC SODA ASH and / or AMC CAUSTIC SODA
- pH levels will remain normal after use
- Easy to use
- Economical.

ASIA PACIFIC

Perth, Australia (Head Office)

T +61 8 9445 4000
E amc@imdexlimited.com

Indonesia

T +62 (0) 21 759 11244

AFRICA

South Africa

T +27 (11) 908 5595

EUROPE

Germany

T +49 4402 6950-0

United Kingdom

T +44 (0) 1273 405 975

SOUTH AMERICA

Argentina

T +54 (9) 261 426 1116

Brazil

T +55 (47) 3404 5920

Chile

T +56 (2) 2589 9300

Peru

T + 51 (1) 322 8850

NORTH AMERICA

USA / Canada

T +801-364-0233

Mexico

T +52 (871) 169 2095