

# EUROGEL XTRA

## VISCOSIFIERS



### Description

EUROGEL XTRA is an easy to mix, one-sack drilling fluid system that provides various beneficial rheological and filtration properties. EUROGEL XTRA is designed for use in horizontal directional drilling, water well, mining and tunneling applications.

### Application

EUROGEL XTRA increases borehole cleaning and stabilization properties in freshwater drilling fluid. EUROGEL XTRA should be added through a hopper. The recommended mixing and hydration time is 10 – 15 minutes.

### Typical Physical Properties

Appearance: Greenish tan powder  
Specific gravity: 2.3 – 2.6

### Recommended Treatment

APPLICATION	KG / M <sup>3</sup>
Normal drilling conditions	15 – 23
Sand	23 – 28
Unconsolidated formations	28 – 35

*Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.*

### Advantages

- Rapidly yields
- Economical
- Assists in borehole stabilisation
- Enhances fluid loss control
- Environmentally acceptable.

#### ASIA PACIFIC

Perth, Australia (Head Office)

T +61 8 9445 4000

E [amc@imdexlimited.com](mailto:amc@imdexlimited.com)

Indonesia

T +62 (0) 21 759 11244

#### AFRICA

South Africa

T +27 (11) 908 5595

#### EUROPE

Germany

T +49 4402 6950-0

United Kingdom

T +44 (0) 1273 405 975

#### SOUTH AMERICA

Argentina

T +54 (9) 261 426 1116

Brazil

T +55 (47) 3404 5920

Chile

T +56 (2) 2589 9300

Peru

T + 51 (1) 322 8850

#### NORTH AMERICA

USA / Canada

T +801-364-0233

Mexico

T +52 (871) 169 2095