

AMC EZEE BORE™

VISCOSIFIERS



Description

AMC EZEE BORE™ is an easy to mix, high quality bentonite based product that provides excellent rheological and filtration control properties and is ideally suited for use in horizontal directional drilling, water well, mining and tunnelling applications.

Application

AMC EZEE BORE™ increases borehole cleaning and formation stabilization in freshwater drilling fluid. AMC EZEE BORE™ should be added through a hopper and allowed to mix for 10 – 15 minutes so that the product can fully yield.

Typical Physical Properties

Appearance: Light yellow to amber powder
 Solubility: Insoluble in water
 Specific gravity: 2.3 – 2.6
 pH (2.5% solution): 7.5 – 9.5

Recommended Treatment

APPLICATION	KG / M³	LB / BBL
Normal drilling conditions	15 – 23	5 – 8
Sand	23 – 28	8 – 10
Unconsolidated formations	28 – 35	10 – 12.5

Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.

Advantages

- Rapidly yields
- Economical
- Assists in borehole stabilisation
- Provides excellent hole cleaning
- Enhances fluid loss control
- Environmentally acceptable.

ASIA PACIFIC

Perth, Australia (Head Office)

T +61 8 9445 4000
 E amc@imdexlimited.com

Indonesia

T +62 (0) 21 759 11244

AFRICA

South Africa

T +27 (11) 908 5595

EUROPE

Germany

T +49 4402 6950-0

United Kingdom

T +44 (0) 1273 405 975

SOUTH AMERICA

Argentina

T +54 (9) 261 426 1116

Brazil

T +55 (47) 3404 5920

Chile

T +56 (2) 2589 9300

Peru

T + 51 (1) 322 8850

NORTH AMERICA

USA / Canada

T +801-364-0233

Mexico

T +52 (871) 169 2095