

AMC TRUCK WASH™

FOAMING AGENTS & DETERGENTS



Description

AMC TRUCK WASH™ is a high foaming degreasing detergent which effectively removes dirt, oil, and grease from surfaces.

Application

AMC TRUCK WASH™ is suitable for maintenance cleaning in the workshop, factory, mining maintenance and processing areas. It can also be used for removing oil from roads and off-road vehicles and equipment.

Typical Physical Properties

Appearance: Clear liquid
 Solubility in water: Miscible
 pH (as supplied): 8 – 9.5
 Specific gravity: 1 – 1.1

Recommended Treatment

APPLICATION	RATIO
Degreasing engines and machinery	1:1 to 1:4
Vehicle / equipment washing	1:19
Concrete floors and steel surfaces	1:40
Pressure cleaning	1:30 to 1:80

For best results first hose down surfaces to remove heavy deposits. It is best to use AMC TRUCK WASH™ on cool surfaces. Apply the cleaning solution directly to surfaces. Allow time for the detergent to penetrate (5 – 10min). Rinse off with a high-pressure water cleaner.

Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.

Advantages

- Easy to apply
- Safe to use
- Helps to extend the life of vehicle and equipment paint and panel work.

ASIA PACIFIC

Perth, Australia (Head Office)

T +61 8 9445 4000
 E amc@imdexlimited.com

Indonesia

T +62 (0) 21 759 11244

AFRICA

South Africa

T +27 (11) 908 5595

EUROPE

Germany

T +49 4402 6950-0

United Kingdom

T +44 (0) 1273 483 700

SOUTH AMERICA

Argentina

T +54 9 261 211 3676

Brazil

T +55 (47) 3404 5920

Chile

T +56 (2) 2589 9300

Peru/Ecuador

T + 51 (1) 322 8850

NORTH AMERICA

USA / Canada

T +801-364-0233

Mexico

T +52 (871) 169 2095